

CMG160F/CMG160L/CMG160V

Semi-Flex, Low-Loss, Optional FEP & LSOH & PVC Jacket,
Coaxial Cable



Structure & Dimension

	Structure	Part No.	Dimension (mm)	Material
1	Inner Conductor		1.08	Silver Plated Copper/Silver Plated Copper Clad Steel
2	Insulating		3.50	PTFE
3	Outer Conductor		4.10	Tinned Copper Braid
		CMG160F	4.70	FEP
4	Jacket	CMG160L	4.90	LSOH
		CMG160V	4.90	PVC

Specification

1	Operating Frequency (GHz)	20
2	Impedance (Ohms)	50
3	Velocity of Propagation	70%
4	Time Delay (ns/m)	4.7
5	Capacitance (pF/m)	95
6	Voltage Withstand (V, DC)	2100
7	Shielding Effectiveness (dB)	>100
8	Single Bend Radius (mm)	10.00
9	Repeated Bend Radius (mm)	40.00
		-55~+125 (FEP Jacket)
10	Temperature Range (°C)	-40~+80 (LSOH Jacket)
		-25~+70 (PVC Jacket)

Attenuation VS. Frequency VS. Power

Frequency (MHz)	500	1000	5000	10000	18000	20000
Attenuation (dB/m)	0.231	0.358	0.889	1.330	1.912	1.947
Average Power (KW)	0.657	0.412	0.180	0.125	0.093	0.086



Add: 569 Huaxu Road, Qingpu Shanghai, P.R.China

Tel: +86-021-54667179

Email: sales@mechanc.com

Web: www.mechanc.com